

# Catching Frame Development for a Citrus Harvest System

By

G. E. COPPOCK  
Agricultural Engineer  
Fla. Dept. of Citrus  
University of Florida, IFAS  
Agricultural Research and Education  
Center  
P. O. Box 1088  
Lake Alfred, Fla. 33850

In 1975, Florida citrus plantings totaled 330.8 thousand hectares (817.3 thousand acres), which produced 9.3 million metric tons (230.3 million boxes) of fruit. Approximately 85 percent of this production was processed into products (reference 4). The crop was harvested almost entirely by hand labor.

Florida citrus industry has been searching for several years for ways to avoid total dependency on seasonal labor for harvesting the crop. Mechanical systems have been developed for fruit destined to be processed into products, but have had very limited industry acceptance (Coppock 1969). The main reason has been the low economic justification obtained under a wide range of conditions.

Limb shaker-catching frame harvest systems similar to those successful in other tree crop industries have shown considerable merit in citrus, especially when assisted by an abscission chemical to loosen the fruit (Coppock and Hedden 1968) (Wilson 1969). A problem in the acceptance of those systems has been in the development of a catching frame to fit a wide range of operating conditions without becoming too expensive, fragile, complex or bulky for effective performance. A "catch-dump" catching frame concept was conceived which showed promise of simplifying the frame design without limiting its function. A review of

developments leading up to the "catch-dump" concept, the development of the concept into a harvest system and the system's performance are reported in this paper.

The main thrust of powered catching frame development began about 1960 when light-weight inertia shakers suitable for mounting on frames were developed. In 1968, Coppock and Hedden reported on an experimental shaker-catching frame harvest system. It employed two tractor-drawn frames, one for each side of a tree with a limb shaker mounted on each frame which swung into the tree diagonally across from each other. One frame contained fruit handling conveyors and the other permitted the fruit to move across a seal onto that frame. Fruit from both halves of the tree was temporarily stored in a wire basket located on the frame having the fruit handling conveyors. Coppock 1967, reported on another version of this harvest system where the shakers swung into the tree from one side of the tree rather than diagonally and where the fruit was stored in a bin located on one frame rather than in wire baskets. Later the frames were changed to incorporate a fruit conveyor in each frame with a crossover conveyor at one end. This enabled each frame to operate independently which eliminated the neces-

Continued on Page 32

Florida Agricultural Experiment Station  
Journal Series No.  
Cooperative research by the Florida Department of Citrus, AREC, University of Florida, Lake Alfred, and U. S. Department of Agriculture.

Ask Your  
Chemical Supplier  
About...

**KE-O-NU**<sup>TM</sup>

Florida Made for the Agri-Trade

**TOWER**

CHEMICAL COMPANY



Montverde Rd. and SCL  
CLERMONT, FL. 32711

(305) 656-2333



## PROGRAM YOUR COVERAGE WITH AgTec

**Save** — covers to 60  
acres of grove in 8 hrs.

**Low Volume — Fast  
Set Up** — any pattern  
you need in minutes,  
and it holds the pattern  
with delivery as low as  
10 gallons per acre.

**Model Size** — one just  
right for your grove —  
3-pt's — 2 diesel  
engines — most popular  
Florida Model illustrated.



**Call Your  
AgTec Dealer Now!**

Pounds Motor Co.  
Winter Garden  
Call Russell  
(305) 656-1352

Central Florida  
Spray Equip. Co.  
Winter Haven  
Call Howard  
(813) 293-3150  
or John (813) 453-3842

P&P Tractor Co.  
Okeechobee  
(813) 763-6424

